Guangzhou Four E's Scientific Co., Ltd

5th floor, Building C, No. 2, Ruitai Road,
Huangpu District, Guangzhou, 510535, Guangdong, China
Tel: 86-20-3803 2775; Fax: 86-20-3803 2771

Mini Magnetic Stirrer

Features:

- Speed range of 15-1500rpm
- High IP protection class (IP 65)
- Automatic reverse rotation for excellent mixing performance
- Set-up plate and casing are made from chemically resistant materials
- Slip-proof and stable stand

Specifications:

Model	**MI0102001**
Rated voltage [V AC]	100-240
Rated Frequency [Hz]	50-60
Output Voltage [V DC]	12
Output Power [W]	Min.3
Stirring Mechanism	coil drive
Speed Range [rpm]	15-1500
Stirred Quantity (max) [ml]	800
Operating time [%]	100
Protection Class	II
Pollution Degree	2
Overvoltage Category	II
EN 60529 Protection Class	IP 65
Ambient Humidity (Relative) [%]	80
Ambient Temperature [°C]	5 to 40 (in the operation)
Transport Temperature [°C]	-25 to +70
Storage Temperature [°C]	-10 to +70
Material	Front membrane sheet Polyester
Weight [kg]	0.35
Installed Weight (max) [kg]	2
Set-up surface [mm]	Φ100
Dimensions (W x D x H) [mm]	115 x 175 x 12