Basic Peristaltic Pump

WT600-3J

Flow Rates

20000 mL/min

4.2-12000 mL/min



Pump Head Options



YZ1515x
YZ2515x



YZII15
YZII25



KZ25



DG15-24

PERISTALTIC PUMP

Speed	60rpm-600rpm, CW/CCW.
Speed resolution	1rpm
Speed accuracy	≤±1%
Control mode	Membrane keypad, external signal control and communication control are available.
Display	3-digit LED display for current speed, 4 LED indicators for operating status.
External control	Start/stop, direction and speed control (4-20mA, 0.5-5V, 1-10V, 1-10kHz external control module optional).
Communication interface	RS485
Power-off memory	Return to previous status when powered on
Prime	For fast filling and emptying at full speed
Dimension (L×W×H)	273×190×272 (mm)
Power supply	AC 220V±20%/200W or AC 110V±20%/200W
Operating temperature	0 to 40°C
Relative humidity	<90%
IP rating	IP55
Weight	7.3kg

Mainly used in industrial applications. With brushless motor, can drive multi-pump heads.
Stainless steel housing, high IP rating.



CE LAB INDUSTRIAL Equip with FK-1C to realize dispensing function

Model (Product code,Power supply,Speed control signal)	Pump Head	Tubing	Flow Rate (mL/min)	Weight (kg)
WT600-3J-A (05.02.64A, AC220V, 0.5-5V) WT600-3J-B (05.02.64B, AC220V, 1-10V) WT600-3J-C (05.02.64C, AC220V, 4-20mA) WT600-3J-D (05.02.64D, AC220V, 1kHz-10kHz) WT600-3J-E (05.02.64E, AC220V, RS485) WT600-3J-F (05.02.64F, AC110V, 0.5-5V) WT600-3J-G (05.02.64G, AC110V, 1-10V) WT600-3J-H (05.02.64H, AC110V, 4-20mA) WT600-3J-J (05.02.64J, AC110V, 1kHz-10kHz) WT600-3J-K (05.02.64K, AC110V, RS485)	(1, 2, 3, 4)×YZ1515x	13# 14# 19# 16#	4-2200 (Single Channel)	7.7-8.9
	(1, 2, 3, 4)×YZII15	25# 17# 18#		
	(1, 2, 3, 4)×YZ2515x	15# 24#	100-1600 (Single Channel)	
	(1, 2)×YZII25	15# 24# 35# 36#	100-3000 (Single Channel)	7.7-8.1
	DG15-24	16# 25# 17#	50-1800 (Single Channel)	8.1
	(1, 2)×KZ25	15# 24# 35# 36#	200-6000 (Single Channel)	8.1-8.9