# Water Baths - 2L / 5L / 13L

# WB101 / WB201 / WB301

Four E's is on the cutting edge of water bath technology. These precision heating devices are microprocessor controlled with a sleek glass touch panel interface, and a bright modern digital display. The basin is manufactured from a single piece of durable stainless-steel that is resistant to corrosion and easily cleanable. Available in many sizes with 3 programmable setpoints and timing capabilities. Water baths have multiple built in safety features for years of seamless operation.




Features

- Easy to read LED display
- Adjustable temperature range
- Precise temperature control
- User-friendly glass panel touch interface
- Dry-start protection feature for improved safety
- Over-temperature cut-off & alarm to protect samples from over heating
- Programmable modes can store up to 3 programs
- Durable stainless-steel chamber
- Timed operation capable
- Easy to switch temperature unit between fahrenheit (˚F) and celcius (˚C)

4E's USA

A FOUR E'S SCIENTIFIC® COMPANY

51B Everett Drive, Suite B-10
West Windsor, NJ 08550
Tel: (855).943.3344
Email: info@4Es-USA.com
Web: www.4Es-USA.com

# Water Baths - 2L / 5L / 13L

# WB101 / WB201 / WB301







| Specifications | | | |
|---|---|---|---|
| Model | WB101 | WB201 | WB301 |
| Reservoir Capacity | 2L | 5L | 13L |
| Heating Temperature Range | RT +5˚C to 99.9˚C | RT +5˚C to 99.9˚C | RT+5˚C to 99.9˚C |
| Over Temperature Cut-off | Yes | Yes | Yes |
| Dry-Start Protection | Yes | Yes | Yes |
| Temperature Stability | ± 0.5˚C | ± 0.5˚C | ± 0.3˚C |
| Temperature Display Accuracy | 0.1˚C | 0.1˚C | 0.1˚C |
| Chamber dimensions (L x W x D) | 150 x 138 x 150mm | 300 x 150 x 150mm | 500 x 300 x 200mm |
| Temperature Display | LED | LED | LED |
| Time Display | LED | LED | LED |
| Time Setting Range | 1-999min | 1-999min | 0~99H59min |
| Dimensions (L x W x H) | 252 x 188 x 285mm | 394 x 188 x 285mm | 347.5 x 349 x 426.5mm |
| Weight | 3 kg | 4.5 kg | 7.3 kg |
| Input | 200-240VAC, 50/60HZ<br>100-120VAC, 50/60HZ | 200-240VAC, 50/60HZ<br>100-120VAC, 50/60HZ | 200-240VAC, 50/60HZ<br>100-120VAC, 50/60HZ |
| Power | 200 W | 450 W | 1000 W |


4E's USA

A FOUR E'S SCIENTIFIC® COMPANY

51B Everett Drive, Suite B-10
West Windsor, NJ 08550
Tel: (855).943.3344
Email: info@4Es-USA.com
Web: www.4Es-USA.com